

Stream Nozzles

The stream nozzles have been replaced by MP Rotator.

OPERATING SPECIFICATIONS

- Recommended operating pressure: 30 PSI
- Pair with Pro-Spray PRS30 pop-up for pressure regulation to 30 PSI
- Warranty period: 2 years



MODEL S-8A STREAM SPRAY NOZZLES PERFORMANCE CHART

Arc	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM	■	▲
90° 	20	7	0.29	2.28	2.63
	25	8	0.32	1.93	2.22
	30	8	0.38	2.11	2.43
	35	8	0.41	2.29	2.64
	40	9	0.54	1.95	2.25
180° 	20	7	0.54	2.12	2.45
	25	8	0.57	1.71	1.98
	30	8	0.60	1.80	2.08
	35	8	0.63	1.89	2.19
	40	9	0.66	1.57	1.81
360° 	20	7	1.08	2.12	2.45
	25	8	1.11	1.67	1.93
	30	8	1.15	1.73	2.00
	35	8	1.18	1.77	2.05
	40	9	1.22	1.45	1.67

Bold = Recommended pressure

MODEL S-16A STREAM SPRAY NOZZLES PERFORMANCE CHART

Arc	Pressure	Radius	Flow	Precip in/hr	
Blue •	PSI	ft	GPM	■	▲
90° 	20	15	0.40	0.68	0.79
	25	16	0.46	0.69	0.80
	30	16	0.50	0.75	0.87
	35	17	0.54	0.72	0.83
	40	18	0.57	0.68	0.78
180° 	20	15	0.67	0.57	0.66
	25	16	0.80	0.60	0.69
	30	16	0.88	0.66	0.76
	35	17	0.97	0.65	0.75
	40	18	1.04	0.62	0.71
360° 	20	15	1.19	0.51	0.59
	25	16	1.46	0.55	0.63
	30	16	1.66	0.62	0.72
	35	17	1.82	0.61	0.70
	40	18	1.99	0.59	0.68

Bold = Recommended pressure

Adjustable: 25° to 360° • Recommend use of the PRS30 for optimal pressure of 30 PSI

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/irrigation-product/stream-nozzles>
060224