


DETAIL LEGEND:

- | | |
|--|--|
| <p>① TTS800-DD POP-UP ROTOR, 2-STATION DECODER</p> <p>② DECODER/SOLENOID ASSEMBLY INSIDE TTS COMPARTMENT</p> <p>③ HUNTER SWING JOINT ASSEMBLY (HSJ). INSTALL SWING JOINT LAY ARM AT 30° - 45° ANGLE TO THE LATERAL LINE.</p> <p>④ LATERAL LINE FITTING PER PLAN.</p> <p>⑤ LATERAL LINE PER PLAN. SOIL DEPTH PER PLAN.</p> <p>⑥ 1½" [40 mm] MALE ACME</p> | <p>⑦ HUNTER TWO-WIRE CABLE</p> <p>⑧ WIRE SPLICE IN TTS COMPARTMENT</p> <p>⑨ TWO-WIRE PATH</p> <p>⑩ CONTROL WIRE TO SECOND ROTOR HEAD</p> <p>⑪ DECODER WIRE</p> <p>⑫ FINISHED GRADE</p> |
|--|--|

**TTS-800-DD 2-STATION DECODER
VALVE-IN-HEAD ROTOR**



Hunter® HUNTER FILE NO.

NOT TO SCALE
REV: 2019-06-24