

## WATER REQUIREMENT

## IRRIGATION LEGEND

HUNTER I-40-04-SS-B-XX/I-,
#8 @ 5.0 Bars - 38.2 l/min 14.3m RADIUS
#13 @ 5.5 Bars - 49.3 l/min 15.8m RADIUS
#15 @ 5.5 Bars - 68.9 l/min 18.0m RADIUS
#23 @ 5.5 Bars - 92.7 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 20.4m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 20.4m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 20.4m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 20.4m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 20.4m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#23 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#24 @ 5.5 Bars - 90.8 l/min 19.8m RADIUS
#25 @ 6.5 Bars - 90.8 l/min 19.8m RADIUS
#25 @ 6.5 Bars - 90.8 l/min 19.8m RADIUS
#25 @ 6.5 Bars - 90.8 l/min 19.8m RADIUS
#25 @ 6.5 Bars - 90.8 l/min 19.8m RADIUS
#25 @ 6.5 Bars - 90.8 l/min 19.8m RADIUS
#25 @ 6.5 Bars - 90.8 l/min 19.8m RADIUS
#25 @ 6.5 Bars - 90.8 l/min 19.8m RADIUS
#26 @ 6.5 Bars - 90.8 l/min 19.8m RADIUS
#27 @ 70 SYSTEM l/min 19.8m RADIUS
#26 #27 # 70 SYSTEM l/min 19.8m RADIUS
#27 # 70 SYSTEM l/min 19.8m RADIUS

HUNTER FLOW SENSOR IN LINE SIZED FLOW CLIK TEE "FCT"

## **IRRIGATION NOTES**

A9 278 1.5"

- SPRINKLER LOCATIONS ARE TO SCALE
   PIPE LOCATIONS ARE DIAGRAMMATIC
   ALL SPRINKLERS TO BE INSTALLED ON 32mm SCH 80 SWING
- ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS RECOMMENDATIONS
   MAINLINE DEPTH TO BE NO LESS THAN 460mm
   LATERAL DEPTH TO BE NO LESS THAN 100mm
   ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE D AS PER MANUFACTURERS

- 8. LOCATE VALVES/QCV'S OUT OF HIGH TRAFFIC AREAS
  9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF
  10. QCV TO BE LOCATED IN 10" VALVE BOX
  11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
  12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE, FEDERAL CODES
  13. REFER TO HUNTER INSTALLATION DETAILS
  14. REFER TO HUNTER CATALOG FOR PERFORMANCE
- SPECIFICATIONS
- 15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
  16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

## VALVE ID GUIDE

STATION NUMBER

PRECIPITATION RATE mm/hr VALVE SIZE

Hunter Industries offers indemnity, expressed or imp variables of every system consulted.

this plan as a general guide for estimating purposes and offers no piled, for projects installed from this plan. Because of the many nand of every site we recommend that a qualified irrigation designer be

ល៉ា ល៉ា ល៉ា

SHEET

 $_{\rm F}$ 

SYSTEM PERFORMANCE

OFFICIAL BASEBALL FIELD

I-40 FOUR ROW DESIGN LOOPED MAINLINE



Hunter Industries 1940 Diamond Street San Marcos, California 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com