

Hunter Industries offers this plan as a general guide for estimating purposes and offers no indemnity, expressed or implied, for projects installaed from this plan. Because of the many variables of every system and of every site we recommend that a qualified infigation designer be consulted.

SCALE

1" = 80'

120'

SHEET

1 OF 1

Hunter Industries 1940 Dlamond Street San Marcos, Callfornia 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com

| | 823**00•** 

HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR WATER METER MINIMUM SIZE @ 48 GPM IS 1.5" BACKFLOW PREVENTER SIZED TO SYSTEM GPM

HUNTER ACC-1200 SOLID STATE METAL CABINET CONTROLLER HUNTER ICV/IBV ELECTRIC CONTROL VALVE SIZE AS SHOWN HUNTER HQ-44-XX-AW QUICK COUPLER VALVE (OPTIONAL)

5. MAINLINE DEPTH TO BE NO LESS THAN 18"
6. LATERAL DEPTH TO BE NO LESS THAN 16"
7. ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE BOX
8. LOCATE VALVES/QCV'S OUT OF HIGH TRAFFIC AREAS
9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF
10. QCV TO BE LOCATED IN 10" VALVE BOX
11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM

RECOMMENDATIONS

NOZZLE PERFORMANCE: #3.5 @ 40 PSI - 3.0 GPM 38' RADIUS #8 @ 40 PSI - 6.0 GPM 41' RADIUS

HUNTER FLOW SENSOR IN LINE SIZED FLOW CLIK TEE "FCT"

13. REFER TO HUNTER INSTALLATION DETAILS
14. REFER TO HUNTER CATALOG FOR PERFORMANCE SPECIFICATIONS

12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE,

FEDERAL CODES

15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

ISOLATION VALVE LINE SIZED

MAINLINE PIPE LATERAL PIPE

LOOPED MAINLINE