



LEGEND:

- 1 ECO-MAT PER PLAN - CUT MAT TO FIT LIMITS OF PLANTED AREA
- 2 FLUSH POINT (PLD-BV) IN SUBTERRANEAN BOX PER PLAN
- 3 ECO-INDICATOR ON SWING ARM
- 4 PVC EXHAUST HEADER - SIZE PER PLAN
- 5 AIR RELIEF VALVE IN VALVE BOX
- 6 PVC TO DRIP LINE TUBING CONNECTION (PLD OR PLD-LOC FITTINGS) TYP.
- 7 DRIP CONTROL ZONE KIT PER PLAN
- 8 PVC SUPPLY HEADER - SIZE PER PLAN
- 9 ECO-WRAP CONNECTIONS

NOTES

AIR RELIEF VALVE (PLD-AVR) INSTALLED IN VALVE BOX AT OPTIMAL HIGHEST POINT FROM CONTROL ZONE KIT. MULTIPLE AIR RELIEF VALVES MAY BE NEEDED TO ACCOMMODATE DIFFERENCES IN GRADE.

ECO-INDICATOR TO BE INSTALLED AT OPTIMAL FURTHEST POINT FROM CONTROL ZONE KIT IN CLEAR VIEW WHEN POPPED UP.

FLUSH POINT TO BE INSTALLED AT OPTIMAL FURTHEST POINT FROM CONTROL ZONE KIT TO ALLOW FOR MAXIMUM DEBRIS FLUSH IN SYSTEM.