

ST-90

The ST-90 synthetic turf rotor is designed for installation in natural turf adjacent to the playing surface — the perfect solution for small and midsize fields.

KEY BENEFITS

- Flexible arc adjustment from 40° to 360° offers narrow-to-wide coverage
- QuickCheck™ Arc Mechanism lets you verify the arc setting without waiting for the sprinkler to finish its rotation
- Through-the-top arc adjustment allows you to easily set the arc at the sprinkler head
- Water-lubricated gear drive delivers reliable operation without clogging
- Factory-installed rubber logo cap increases athlete safety on the field
- Nozzle trajectory: 22.5°



OPERATING SPECIFICATIONS

- Radius: 103' to 120'
- Flow: 74.5 to 92.0 GPM
- Operating pressure range: 100 to 120 PSI
- Precipitation rate: 1.25 in/hr approximately
- Warranty period: 5 years for component parts

USER-INSTALLED OPTIONS

- Rubber Cover Kit ST-90: P/N 234200

| STG-900 NOZZLE PERFORMANCE DATA | | | | | |
|---|-----------------|---------------|-------------|--------------|------|
| Nozzle | Pressure PSI | Radius ft. | Flow GPM | Precip in/hr | |
| | | | | ■ | ▲ |
| 73 • Orange | 100 | 103 | 74.5 | 1.35 | 1.56 |
| | 110 | 109 | 77 | 1.25 | 1.44 |
| | 120 | 115 | 79.6 | 1.16 | 1.34 |
| 83 • Tan | 100 | 112 | 84.2 | 1.29 | 1.49 |
| | 110 | 116 | 88.1 | 1.26 | 1.46 |
| | 120 | 120 | 92 | 1.23 | 1.42 |
| Notes: All precipitation rates calculated for 180 degree operation. For precipitation rate of 360 degree sprinkler divide by 2. Requires minimum 100 PSI dynamic pressure supplied to swing joint inlet. | | | | | |

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/en-metric/node/152501052624>