

PS Ultra

The PS Ultra is a compact, slim-line spray sprinkler with the option of preinstalled nozzles for faster installation.

KEY BENEFITS

- Enhanced cap for more durability, easier handling, and extended riser seal life
- Large inlet filter screen for increased debris resistance
- Heavy-duty spring for consistent riser retraction
- Directional flush plug design for cleaner installation
- Two-piece ratcheting riser
- Check valve option eliminates low-head drainage
- 5 cm and 10 cm models can retrofit into older style PS models
- Compatible with all female-threaded nozzles

Operating Specifications

- Operational pressure range: 1.4 to 4.8 bar; 140 to 480 kPa
- Warranty period: 2 years

Factory-Installed Options

- Flush plug (large filter screen not included)
- Nozzles: 2.4 m, 3.0 m, 3.7 m, 4.6 m, 5.2 m, 1.5 x 9.1 m side strip
- Large inlet filter screen included in 10 cm and 15 cm preinstalled nozzle models

User-Installed Options

- Check valve installs in filter screen for 10 cm and 15 cm models (up to 2 m of elevation P/N: 462237SP)
- Large inlet filter screen P/N: 162900SP
- Shutoff nozzle P/N: 916400SP



		NOZZLE 4A LT. GREEN •					NOZZLE 6A LT. BLUE •					
		1.2 m radius			1.8 m radius							
		Adjustable from 0° to 360			Adjustable from 0° to 360							
		Trajectory 0°			Trajectory 0°							
Arc	Pressure	Radius	Flow		Precip mm/hr	Radius	Flow		Precip mm/hr			
	bar kPa	m	m³/hr	l/min	[■]	▲	m	m³/hr	l/min	[■]	▲	
45°	1.0	100	0.9	0.02	0.31	187	216	1.5	0.03	0.54	117	136
	1.5	150	1.0	0.02	0.39	178	206	1.6	0.04	0.60	108	124
	2.1	210	1.2	0.03	0.48	167	193	1.8	0.04	0.65	98	114
	2.5	250	1.3	0.03	0.56	158	183	1.9	0.04	0.70	92	106
	3.0	300	1.4	0.04	0.64	149	172	2.1	0.05	0.75	86	99
90°	1.0	100	0.9	0.04	0.72	213	246	1.5	0.06	1.08	116	134
	1.5	150	1.0	0.05	0.76	182	210	1.6	0.07	1.21	109	126
	2.1	210	1.2	0.05	0.83	139	160	1.8	0.08	1.35	102	118
	2.5	250	1.3	0.05	0.91	129	149	1.9	0.09	1.47	97	112
	3.0	300	1.4	0.06	0.95	116	134	2.1	0.10	1.61	92	106
120°	1.0	100	0.9	0.06	0.97	221	255	1.5	0.08	1.26	102	118
	1.5	150	1.0	0.07	1.10	188	217	1.6	0.09	1.43	97	112
	2.1	210	1.2	0.07	1.25	162	187	1.8	0.10	1.61	91	105
	2.5	250	1.3	0.08	1.36	146	168	1.9	0.11	1.76	87	100
	3.0	300	1.4	0.09	1.49	131	151	2.1	0.12	1.93	82	95
180°	1.0	100	0.9	0.07	1.18	178	206	1.5	0.10	1.70	92	106
	1.5	150	1.0	0.08	1.38	157	181	1.6	0.12	1.96	88	102
	2.1	210	1.2	0.10	1.60	139	160	1.8	0.13	2.24	84	97
	2.5	250	1.3	0.11	1.78	127	146	1.9	0.15	2.47	81	94
	3.0	300	1.4	0.12	1.98	115	133	2.1	0.16	2.72	78	90
240°	1.0	100	0.9	0.12	1.94	220	254	1.5	0.15	2.44	99	114
	1.5	150	1.0	0.13	2.24	192	221	1.6	0.17	2.83	96	111
	2.1	210	1.2	0.16	2.59	168	194	1.8	0.20	3.28	92	107
	2.5	250	1.3	0.17	2.86	153	177	1.9	0.22	3.63	89	103
	3.0	300	1.4	0.19	3.17	139	160	2.1	0.24	4.03	86	99
270°	1.0	100	0.9	0.13	2.09	211	244	1.5	0.18	3.08	111	128
	1.5	150	1.0	0.14	2.40	183	211	1.6	0.21	3.52	106	122
	2.1	210	1.2	0.16	2.75	159	183	1.8	0.24	4.02	101	116
	2.5	250	1.3	0.18	3.02	144	166	1.9	0.27	4.42	97	112
	3.0	300	1.4	0.20	3.33	130	150	2.1	0.29	4.87	92	107
360°	1.0	100	0.9	0.14	2.26	171	197	1.5	0.21	3.57	96	111
	1.5	150	1.0	0.16	2.60	148	171	1.6	0.24	4.07	92	106
	2.1	210	1.2	0.18	2.98	129	149	1.8	0.28	4.62	87	100
	2.5	250	1.3	0.20	3.29	117	135	1.9	0.30	5.06	83	96
	3.0	300	1.4	0.22	3.63	106	122	2.1	0.33	5.56	79	92

		NOZZLE 8A BROWN •					NOZZLE 10A RED •					
		2.4 m radius Adjustable from 0° to 360 Trajectory 15°				3.0 m radius Adjustable from 0° to 360 Trajectory 15°						
Arc	Pressure	Radius	Flow	Precip mm/hr	Radius	Flow	Precip mm/hr					
45°	bar	kPa	m	m³/hr	l/min	■	▲	m	m³/hr	l/min	■	▲
	1.0	100	2.0	0.04	0.62	77	89	2.6	0.04	0.68	49	56
	1.5	150	2.2	0.04	0.72	72	83	2.8	0.05	0.80	49	57
	2.1	210	2.4	0.05	0.83	67	77	3.0	0.06	0.94	49	56
	2.5	250	2.6	0.05	0.91	63	73	3.2	0.06	1.06	48	56
90°	3.0	300	2.9	0.06	1.01	59	68	3.5	0.07	1.18	47	54
	1.0	100	2.0	0.07	1.24	77	89	2.6	0.08	1.35	49	56
	1.5	150	2.2	0.09	1.44	72	83	2.8	0.10	1.61	49	57
	2.1	210	2.4	0.10	1.65	67	77	3.0	0.11	1.89	49	56
	2.5	250	2.6	0.11	1.82	63	73	3.2	0.13	2.11	48	56
120°	3.0	300	2.9	0.12	2.02	59	68	3.5	0.14	2.37	47	54
	1.0	100	2.0	0.10	1.66	77	89	2.6	0.11	1.80	49	56
	1.5	150	2.2	0.11	1.92	72	83	2.8	0.13	2.14	49	57
	2.1	210	2.4	0.13	2.20	67	77	3.0	0.15	2.52	49	56
	2.5	250	2.6	0.15	2.43	63	73	3.2	0.17	2.82	48	56
180°	3.0	300	2.9	0.16	2.69	59	68	3.5	0.19	3.16	47	54
	1.0	100	2.0	0.15	2.49	77	89	2.6	0.16	2.71	49	56
	1.5	150	2.2	0.17	2.87	72	83	2.8	0.19	3.21	49	57
	2.1	210	2.4	0.20	3.30	67	77	3.0	0.23	3.78	49	56
	2.5	250	2.6	0.22	3.65	63	73	3.2	0.25	4.23	48	56
240°	3.0	300	2.9	0.24	4.03	59	68	3.5	0.28	4.73	47	54
	1.0	100	2.0	0.20	3.32	77	89	2.6	0.22	3.61	49	56
	1.5	150	2.2	0.23	3.83	72	83	2.8	0.26	4.28	49	57
	2.1	210	2.4	0.26	4.40	67	77	3.0	0.30	5.03	49	56
	2.5	250	2.6	0.29	4.86	63	73	3.2	0.34	5.64	48	56
270°	3.0	300	2.9	0.32	5.38	59	68	3.5	0.38	6.31	47	54
	1.0	100	2.0	0.22	3.73	77	89	2.6	0.24	4.06	49	56
	1.5	150	2.2	0.26	4.31	72	83	2.8	0.29	4.82	49	57
	2.1	210	2.4	0.30	4.95	67	77	3.0	0.34	5.66	49	56
	2.5	250	2.6	0.33	5.47	63	73	3.2	0.38	6.34	48	56
360°	3.0	300	2.9	0.36	6.05	59	68	3.5	0.43	7.10	47	54
	1.0	100	2.0	0.30	4.97	77	89	2.6	0.32	5.41	49	56
	1.5	150	2.2	0.34	5.75	72	83	2.8	0.39	6.43	49	57
	2.1	210	2.4	0.40	6.61	67	77	3.0	0.45	7.55	49	56
	2.5	250	2.6	0.44	7.29	63	73	3.2	0.51	8.45	48	56
	3.0	300	2.9	0.48	8.07	59	68	3.5	0.57	9.47	47	54

		NOZZLE 12A GREEN •					NOZZLE 15A BLACK •					NOZZLE 17A GREY •					
		3.7 m radius			4.6 m radius			5.2 m radius									
		Adjustable from 0° to 360			Adjustable from 0° to 360			Adjustable from 0° to 360									
		Trajectory 28°			Trajectory 28°			Trajectory 28°									
Arc	Pressure	Radius	Flow		Precip mm/hr	Radius	Flow		Precip mm/hr	Radius	Flow		Precip mm/hr				
	bar	kPa	m	m³/hr	l/min		m	m³/hr	l/min		m	m³/hr	l/min		m	m³/hr	l/min
45°	1.0	100	3.2	0.04	0.73	34	40	4.0	0.08	1.27	38	43	4.6	0.10	1.68	38	43
	1.5	150	3.4	0.06	0.97	40	46	4.3	0.09	1.51	39	45	4.9	0.12	1.94	38	44
	2.1	210	3.7	0.07	1.23	44	51	4.6	0.11	1.79	40	46	5.2	0.13	2.23	39	45
	2.5	250	3.9	0.09	1.44	46	54	4.9	0.12	2.00	40	46	5.5	0.15	2.46	39	45
	3.0	300	4.1	0.10	1.68	48	56	5.2	0.14	2.25	40	46	5.8	0.16	2.72	39	45
90°	1.0	100	3.2	0.09	1.46	34	40	4.0	0.15	2.53	38	43	4.6	0.20	3.36	38	43
	1.5	150	3.4	0.12	1.93	40	46	4.3	0.18	3.03	39	45	4.9	0.23	3.88	38	44
	2.1	210	3.7	0.15	2.46	44	51	4.6	0.21	3.57	40	46	5.2	0.27	4.45	39	45
	2.5	250	3.9	0.17	2.88	46	54	4.9	0.24	4.01	40	46	5.5	0.30	4.92	39	45
	3.0	300	4.1	0.20	3.36	48	56	5.2	0.27	4.50	40	46	5.8	0.33	5.44	39	45
120°	1.0	100	3.2	0.12	1.94	34	40	4.0	0.20	3.38	38	43	4.6	0.27	4.48	38	43
	1.5	150	3.4	0.15	2.58	40	46	4.3	0.24	4.03	39	45	4.9	0.31	5.17	38	44
	2.1	210	3.7	0.20	3.28	44	51	4.6	0.29	4.76	40	46	5.2	0.36	5.94	39	45
	2.5	250	3.9	0.23	3.84	46	54	4.9	0.32	5.34	40	46	5.5	0.39	6.56	39	45
	3.0	300	4.1	0.27	4.48	48	56	5.2	0.36	6.00	40	46	5.8	0.43	7.25	39	45
180°	1.0	100	3.2	0.17	2.91	34	40	4.0	0.30	5.07	38	43	4.6	0.40	6.71	38	43
	1.5	150	3.4	0.23	3.86	40	46	4.3	0.36	6.05	39	45	4.9	0.47	7.75	38	44
	2.1	210	3.7	0.30	4.92	44	51	4.6	0.43	7.14	40	46	5.2	0.53	8.91	39	45
	2.5	250	3.9	0.35	5.76	46	54	4.9	0.48	8.02	40	46	5.5	0.59	9.83	39	45
	3.0	300	4.1	0.40	6.71	48	56	5.2	0.54	9.00	40	46	5.8	0.65	10.87	39	45
240°	1.0	100	3.2	0.23	3.88	34	40	4.0	0.41	6.76	38	43	4.6	0.54	8.95	38	43
	1.5	150	3.4	0.31	5.15	40	46	4.3	0.48	8.07	39	45	4.9	0.62	10.34	38	44
	2.1	210	3.7	0.39	6.56	44	51	4.6	0.57	9.52	40	46	5.2	0.71	11.88	39	45
	2.5	250	3.9	0.46	7.68	46	54	4.9	0.64	10.69	40	46	5.5	0.79	13.11	39	45
	3.0	300	4.1	0.54	8.95	48	56	5.2	0.72	12.00	40	46	5.8	0.87	14.50	39	45
270°	1.0	100	3.2	0.26	4.37	34	40	4.0	0.46	7.60	38	43	4.6	0.60	10.07	38	43
	1.5	150	3.4	0.35	5.80	40	46	4.3	0.54	9.08	39	45	4.9	0.70	11.63	38	44
	2.1	210	3.7	0.44	7.38	44	51	4.6	0.64	10.71	40	46	5.2	0.80	13.36	39	45
	2.5	250	3.9	0.52	8.65	46	54	4.9	0.72	12.03	40	46	5.5	0.89	14.75	39	45
	3.0	300	4.1	0.60	10.07	48	56	5.2	0.81	13.50	40	46	5.8	0.98	16.31	39	45
360°	1.0	100	3.2	0.35	5.83	34	40	4.0	0.61	10.13	38	43	4.6	0.81	13.43	38	43
	1.5	150	3.4	0.46	7.73	40	46	4.3	0.73	12.10	39	45	4.9	0.93	15.51	38	44
	2.1	210	3.7	0.59	9.84	44	51	4.6	0.86	14.28	40	46	5.2	1.07	17.82	39	45
	2.5	250	3.9	0.69	11.53	46	54	4.9	0.96	16.03	40	46	5.5	1.18	19.67	39	45
	3.0	300	4.1	0.81	13.43	48	56	5.2	1.08	18.00	40	46	5.8	1.30	21.75	39	45

Bold = Recommended pressure

Note: The Pro-Spray PRS30's built-in pressure regulator controls output to a maximum of 2.1 bar; 210 kPa. Adjusting the radius reduction screw may be required to achieve catalogue radius and flow.

STRIP PATTERN NOZZLES PERFORMANCE DATA

• Nozzle Blue

Arc	Pressure		Width x Length	Flow	
	bar	kPa		m³/hr	l/min
SS-530  Side Strip	1.0	100	1.2 x 8.5	0.21	3.50
	1.5	150	1.5 x 9.0	0.25	4.20
	2.0	200	1.5 x 9.0	0.29	4.90
	2.1	210	1.5 x 9.0	0.30	5.00
	2.5	250	1.5 x 9.0	0.33	5.50

Notes = Recommended pressure

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

[https://www.hunterindustries.com/en-metric/irrigation-product/spray-bodies/ps-ultra
052624](https://www.hunterindustries.com/en-metric/irrigation-product/spray-bodies/ps-ultra-052624)