Pro-C®

Simple programming and flexible station expansion make the Pro-C the professional's choice for residential and light commercial systems.

KEY BENEFITS

- Number of stations: Conventional wiring from 4 to 23 stations
- Hybrid EZ Decoder option up to 32 total stations (28 stations maximum if two-wire only)
- 3 independent irrigation programs (4 start times each) allow for customised scheduling
- Two sensor inputs come standard for use with Hunter Clik or Solar Sync™ Sensors
- Large, backlit display for simple programming and manual operation in any light
- Optional Seconds Mode offers precise watering and flexible Run Times
- Prewired with power cord and plug for simple installation in indoor and outdoor applications
- 1 P/MV output for pump start relay and master valve activation
- Dedicated Solar Sync dial position provides logic for smart water savings
- SmartPort™ Wiring Harness ensures quick connection to convenient ROAM and ROAM XL Remotes


Electrical Specifications

Transformer input: 120 VAC or 230 VAC
Transformer output (24 VAC): 1 A
Station output (24 VAC): 0.56 A

• P/MV output (24 VAC): 0.28 A

• Approvals: UL, cUL, FCC, CE, UKCA, RCM

• Warranty period: 2 years



https://www.hunterindustries.com/en-metric/irrigation-product/controllers/pro-cr 052624

