

XC Hybrid

Effectively manage landscapes where electricity is unavailable with this economical battery- or solar-powered controller.

KEY BENEFITS

- Number of stations: 6 or 12
- 3 power options: ambient-light-compatible solar panel, battery, or AC power
- Battery-life indicator for battery replacement
- Stainless steel enclosure protects against vandalism
- 3 programs with 4 start times each and up to 4-hour run times
- Easy Retrieve™ memory backs up the full irrigation schedule
- Delay Between Stations for slow-closing valves or pump recharge
- Seasonal adjustment for quicker schedule adjustments without changing run times
- Solar panel provides maintenance-free operation
- Mounts to flat surfaces or steel posts



Operating Specifications

- Plastic model operates six 1.5V AA alkaline batteries
- Stainless steel model operated by six 1.5V C alkaline batteries
- Stainless steel solar model operates 800 mAh solar panel with charging cell
- All models operate optional 24 VAC plug-in wall adapter (120 VAC P/N 526500, 230 VAC EU P/N 545700, 230 VAC AU P/N 545500)
- Operates DC-latching solenoids (P/N 458200)
- Station output: 9-11 VDC
- P/MV output: 9-11 VDC
- Sensor inputs: 1
- Approvals: Plastic IP24, Stainless Steel IP44, UL, cUL, FCC, CE, RCM
- Warranty period: 2 years

Maximum Wire Runs

Wire Size Max Distance (m)

1.0 mm	168
1.2 mm	265
1.6 mm	420
2.0 mm	670

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/en-metric/irrigation-product/controllers/xc-hybrid>
052424