

G-35-B

With a wide range of performance to choose from, the B Series rotors are easy on the budget

KEY BENEFITS

- Adjustable, shorter-radius model (50° to 360°)

MODEL SPECIFICATIONS

- Full circle/Part circle (50° to 360°)

MODEL VARIATIONS

B = Block checks up to 10' in elevation change

NOZZLE RANGE

- #2 to #12

NOZZLE CHOICE

- 8 multi trajectory (15 - 25 degrees)

OPERATING SPECIFICATIONS

- Discharge rate: 1.9 to 12.8 GPM
- Radius: 18' to 50'
- Pressure range: 40 to 65 PSI
- Pressure rating: 150 PSI



G35B

Overall Height	9"
Pop-up Height	3"
Flange Diameter	4-3/4"
Inlet Size	1-1/4" Female ACME

G835 / G35B NOZZLE PERFORMANCE DATA*

Nozzle	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM		
2 Yellow	40	18	1.9	0.56	0.65
	50	20	2.1	0.51	0.58
	60	22	2.4	0.48	0.55
	65	23	2.6	0.47	0.55
3 Yellow	40	23	3.0	0.55	0.63
	50	25	3.2	0.49	0.57
	60	27	3.5	0.46	0.53
	65	28	3.6	0.44	0.51
4 Yellow	40	25	3.9	0.60	0.69
	50	28	4.1	0.50	0.58
	60	30	4.4	0.47	0.54
	65	31	4.6	0.46	0.53
5 Yellow	40	29	4.7	0.54	0.62
	50	32	5.0	0.47	0.54
	60	33	5.3	0.47	0.54
	65	35	5.4	0.42	0.49
6 Yellow	40	32	6.0	0.56	0.65
	50	35	6.3	0.50	0.57
	60	37	6.6	0.46	0.54
	65	39	6.8	0.43	0.50
8 Yellow	40	36	7.8	0.58	0.67
	50	39	8.0	0.51	0.58
	60	42	8.3	0.45	0.52
	65	43	8.5	0.44	0.51
10 Yellow	40	39	9.7	0.61	0.71
	50	43	10.1	0.53	0.61
	60	45	10.3	0.49	0.57
	65	47	10.5	0.46	0.53
12 Yellow	40	44	12.0	0.60	0.69
	50	47	12.2	0.53	0.61
	60	48	12.5	0.52	0.60
	65	50	12.8	0.49	0.57

Note: *Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral.

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/irrigation-product/golf-rotors/g-35-b-051824>