

G-884

The Perfect Combination of Power, Performance, and Serviceability

KEY BENEFITS

- Adjustable model distinguished by a gray collar that comes factory set in a true full-circle configuration
- Exclusive PressurePort™ Nozzle Technology optimizes incoming pressure at each nozzle to increase consistency and maximize distribution uniformity
- High-torque gear drive is the strongest in the industry to mitigate the challenges of debris infiltration
- Proprietary Filter Sentry™ Mechanism cleans the filter with every opening and closing cycle

Operating Specifications

- Radius: 49' to 97'
- Flow: - 14.2 to 58.5 GPM
- Pressure range: 50 to 100 PSI
- Pressure Rating: 150 PSI - 10 bar

Model Variations

- C** = Check-O-Matic checks up to 25' in elevation change and readily converts to Normally Open Hydraulic with through the top connections
- D** = Decoder Valve-In-Head with all "E" specifications below
- DD** = 2-Station Decoder Valve-In-Head with all "E" specifications below
- E** = Electric Valve-In-Head with adjustable pressure regulation, on-off-auto selector, 190mA (350mA inrush) solenoid with captive plunger and internal downstream bleed.



| | | | | | | | |
|--|--|-----------------------|------|------|------|------|------|
| 100 | 96 | 53.5 | 0.56 | 0.65 | | | |
| Dk. Brown  803610 | 53°  Dk. Blue 833500 | Dk. Blue 833500 | - | - | - | - | - |
| | | | 70 | 91 | 49.8 | 0.58 | 0.67 |
| | | | 80 | 93 | 52.2 | 0.58 | 0.67 |
| | | | 90 | 95 | 55.5 | 0.59 | 0.68 |
| | | | 100 | 97 | 58.5 | 0.60 | 0.69 |

Note: Nozzle plug P/N 315300 installed in the front side of the nozzle housing.

* Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral.

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/irrigation-product/golf-rotors/g-884>

051824