

- IRRIGATION NOTES**
1. SPRINKLER LOCATIONS ARE TO SCALE
 2. PIPE LOCATIONS ARE DIAGRAMMATIC
 3. ALL SPRINKLERS TO BE INSTALLED ON 25mm SCH 80 SWING JOINTS
 4. ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURER RECOMMENDATIONS
 5. MAINLINE DEPTH TO BE NO LESS THAN 460mm
 6. LATERAL DEPTH TO BE NO LESS THAN 410mm
 7. ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE BOX
 8. LOCATE VALVES/OCV'S OUT OF HIGH TRAFFIC AREAS
 9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF
 10. OCV TO BE LOCATED IN 10" VALVE BOX
 11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
 12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE, FEDERAL CODES
 13. REFER TO HUNTER INSTALLATION DETAILS
 14. REFER TO HUNTER CATALOG FOR PERFORMANCE SPECIFICATIONS
 15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
 16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

SYSTEM PERFORMANCE DATA

ZONE	SIZE	FLOW	PR	DU	SC
A1	1.5"	11.5	192	18.3	.79
A1	1.5"	11.5	192	18.3	.79
A2	1.5"	11.5	192	18.3	.79
A3	1.5"	11.5	192	18.3	.79
A3	1.5"	11.5	192	18.3	.79
A4	1.5"	11.5	192	18.3	.79
A5	1.5"	10.1	168	9.9	.79
A5	1.5"	10.1	168	9.9	.79
A6	1.5"	10.1	168	9.9	.79
A6	1.5"	10.1	168	9.9	.79
A7	1.5"	10.1	168	9.9	.79
A7	1.5"	10.1	168	9.9	.79
A8	1.5"	10.1	168	9.9	.79
A8	1.5"	10.1	168	9.9	.79
A9	1.5"	10.1	168	9.9	.79
A9	1.5"	10.1	168	9.9	.79
A10	1.5"	10.1	168	9.9	.79
A10	1.5"	10.1	168	9.9	.79
A11	1.5"	10.1	168	9.9	.79
A11	1.5"	10.1	168	9.9	.79
A12	1.5"	10.1	168	9.9	.79
A12	1.5"	10.1	168	9.9	.79

VALVE ID GUIDE

A1	STATION NUMBER
273	1.5"
190	1.5"

WATER REQUIREMENT

A1	STATION NUMBER
273	1.5"
190	1.5"

WATER REQUIREMENT

AT:


-FIELD ELEVATION

-WITHIN 30m OF FIELD

-DOWNSTREAM OF

BACKFLOW

IS 192 l/min @ 3.93 Bars



Hunter®

MULTI-PURPOSE FIELD

I-20 NINE ROW DESIGN

LOOPED MAINLINE

Hunter Industries
1940 Diamond Street
San Marcos, California 92078
SpecPro Technical Assistance
1-800-319-4796
www.HunterIndustries.com

SHEET

1 OF 1