


WATER REQUIREMENT
 WATER REQUIREMENT AT
 FIELD ELEVATION
 - WITHIN 30M OF FIELD
 - DOWNSTREAM OF BACKFLOW
 IS 192 mm/h @ 4.14 Bars

VALVE ID GUIDE

A1	STATION NUMBER
1.5"	273
1.5"	VALVE SIZE
mm/h	PRECIPITATION RATE mm/h

SYSTEM PERFORMANCE DATA

ZONE	SIZE	FLOW mm ³ /h	PR mm/h	DU	SC (min-approx)	
A1	1.5"	11.5	192	16.5	.82	1.2
A2	1.5"	6.94	182	18.5	.82	1.2
A3	1.5"	192	182	18.5	.82	1.2
A4	1.5"	8.64	144	18.5	.82	1.2
A5	1.5"	11.5	192	9.4	.82	1.2
A6	1.5"	11.5	192	9.4	.82	1.2
A7	1.5"	8.64	144	9.4	.82	1.2
A8	1.5"	8.64	144	9.4	.82	1.2
A9	1.5"	8.64	144	9.4	.82	1.2
A10	1.5"	8.64	144	9.4	.82	1.2



IRRIGATION LEGEND

- PRODUCT DESCRIPTION**
- HUNTER I-20-SS-XX: FULL CIRCLE, NOZZLE AS SHOWN
 - HUNTER I-20-SS-XX, PART CIRCLE, NOZZLE AS SHOWN
- NOZZLE PERFORMANCE:**
- #3.5 @ 3.0 Bars - 12 l/min 11.3m RADIUS
 - #8 @ 3.0 Bars - 24.0 l/min 13.1m RADIUS
- HUNTER I-20-SS-XX: FULL CIRCLE, NOZZLE AS SHOWN**
- HUNTER ICV/IBV ELECTRIC CONTROL VALVE SIZE AS SHOWN
 - HUNTER HQ-44-XX-AW QUICK COUPLER VALVE (OPTIONAL)
 - HUNTER IC-1200-W SOLID STATE METAL CABINET CONTROLLER
 - HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR
 - WATER METER MINIMUM SIZE @ 192 LPM IS 50mm
 - BACKFLOW PREVENTER SIZED TO SYSTEM l/min
- MANLINE PIPE**
- MANLINE PIPE
 - SLEEVING
 - ⊗ ISOLATION VALVE LINE SIZED
 - ⊗ HUNTER FLOW SENSOR IN LINE SIZED FLOW CLK. TEE "CT"

IRRIGATION NOTES

1. SPRINKLER LOCATIONS ARE TO SCALE
2. PIPE LOCATIONS ARE DIAGRAMMATIC
3. ALL SPRINKLERS TO BE INSTALLED ON 25mm SCH 80 SWING JOINTS
4. ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURER'S RECOMMENDATIONS
5. MANLINE DEPTH TO BE NO LESS THAN 460mm
6. LATERAL DEPTH TO BE NO LESS THAN 410mm
7. ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE BOX
8. LOCATE VALVES/OCV'S OUT OF HIGH TRAFFIC AREAS
9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF
10. OCV TO BE LOCATED IN 10" VALVE BOX
11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE, FEDERAL CODES
13. REFER TO HUNTER INSTALLATION DETAILS
14. REFER TO HUNTER CATALOG FOR PERFORMANCE SPECIFICATIONS
15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

Hunter Industries offers this plan as a general guide for estimating purposes and offers no indemnity, expressed or implied, for products installed from this plan. Because of the many variables of every system and of every site we recommend that a qualified irrigation designer be consulted.



SOCCER FIELD 75 x 110M
I-20 SEVEN ROW DESIGN
LOOPED MAINLINE

Hunter Industries
 1940 Diamond Street
 San Marcos, California 92078
 SpecPro Technical Assistance
 1-800-319-4796
 www.HunterIndustries.com

SHEET

1 OF 1