

## G-70-B

With a wide range of performance to choose from, the B Series rotors are easy on the budget



- G-70-B is a dedicated, true full-circle model

### MODEL SPECIFICATIONS

- Full circle

### MODEL VARIATIONS

- B = Block checks up to 10' in elevation change

### NOZZLE RANGE

- #15 to #28

### NOZZLE CHOICE

- 6 standard trajectory (25 degrees)

### OPERATING SPECIFICATIONS

- Discharge rate: 13 to 33.7 GPM
- Radius: 53' to 75'
- Pressure range: 50 to 100 PSI
- Pressure rating: 150 PSI



**G70B**

Overall Height	9"
Pop-up Height	3"
Flange Diameter	4-3/4"
Inlet Size	1-1/4" Female ACME

G870 / G70B NOZZLE PERFORMANCE DATA					
Nozzle	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM	■	▲
15 ° Grey	50	53	13.0	0.45	0.51
	60	54	14.1	0.47	0.54
	65	55	14.8	0.47	0.54
	70	56	15.5	0.48	0.55
	80	58	16.3	0.47	0.54
18 ° Red	50	58	14.2	0.41	0.47
	60	59	15.9	0.44	0.51
	65	60	16.3	0.44	0.50
	70	60	16.9	0.45	0.52
	80	61	17.8	0.46	0.53
20 ° Dk. Brown	60	61	18.8	0.49	0.56
	65	62	19.6	0.49	0.57
	70	63	20.5	0.50	0.57
	80	64	22.0	0.52	0.60
	90	64	23.4	0.55	0.63
23 ° Dk. Green	60	63	20.1	0.49	0.56
	65	65	21.0	0.48	0.55
	70	65	21.9	0.50	0.58
	80	66	23.4	0.52	0.60
	90	67	24.9	0.53	0.62
25 ° Dk. Blue	60	65	21.8	0.50	0.57
	65	67	22.5	0.48	0.56
	70	67	23.6	0.51	0.58
	80	69	25.3	0.51	0.59
	90	71	26.9	0.51	0.59
28 ° Black	70	71	28.1	0.54	0.62
	80	71	29.9	0.57	0.66
	90	73	31.8	0.57	0.66
	100	75	33.7	0.58	0.67

**Note:** \*Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral.

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/cn/node/26221>  
071724