





S-16A							
□	□	□	□	□	□□□ mm/h		
• □□□	bar	kPa	m	□□ l/min	■	▲	
90° 	1.0	100	4.3	0.08	1.4	18	21
	1.5	150	4.6	0.1	1.6	18	21
	2.0	200	5	0.11	1.9	18	21
	2.1	210	5	0.11	1.9	18	21
	2.5	250	5.3	0.13	2.1	18	21
180° 	1.0	100	4.3	0.14	2.3	14	17
	1.5	150	4.6	0.17	2.8	15	18
	2.0	200	5	0.2	3.3	16	18
	2.1	210	5	0.2	3.4	16	19
	2.5	250	5.3	0.23	3.8	16	19
360° 	1.0	100	4.3	0.23	3.9	12	14
	1.5	150	4.6	0.3	5	14	16
	2.0	200	5	0.36	6.1	15	17
	2.1	210	5	0.38	6.3	15	17
	2.5	250	5.3	0.43	7.2	16	18


 □□□□
 □□□□25° □ 360° • □□□ PRS30□□□□ 2.1 bar□□□□□□

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/cn/irrigation-product/sheliushipenzui>
 071824