



??	??	??	??	??	?????MM/HR?		
	bar	kPa	m	m <sup>3</sup> /hr	l/min	■	▲
8 ° (40)	2.5	250	13.1	1.63	27.2	19	22
	3.0	300	13.4	1.80	30.0	20	23
	3.5	350	13.7	1.94	32.3	21	24
	4.0	400	14.0	2.06	34.4	21	24
	4.5	450	14.0	2.18	36.3	22	26
	5.0	500	14.3	2.29	38.2	22	26
	5.5	550	14.6	2.41	40.2	23	26
10 ° (41)	3.0	300	14.6	2.20	36.6	21	24
	3.5	350	14.9	2.37	39.4	21	24
	4.0	400	15.2	2.52	42.0	22	25
	4.5	450	15.5	2.67	44.5	22	25
	5.0	500	15.5	2.81	46.8	23	27
	5.5	550	15.8	2.96	49.3	24	27
	6.0	600	16.2	3.08	51.4	24	27
13 ° (42)	3.0	300	14.9	2.36	39.4	21	24
	3.5	350	15.2	2.55	42.6	22	25
	4.0	400	15.5	2.73	45.5	23	26
	4.5	450	15.5	2.90	48.3	24	28
	5.0	500	15.8	3.06	51.0	24	28
	5.5	550	16.2	3.23	53.9	25	29
	6.0	600	16.5	3.38	56.3	25	29
15 ° (43)	3.0	300	16.2	2.93	48.8	22	26
	3.5	350	16.5	3.19	53.2	24	27
	4.0	400	16.8	3.44	57.3	24	28
	4.5	450	17.1	3.67	61.2	25	29
	5.0	500	17.4	3.89	64.9	26	30
	5.5	550	18.0	4.14	68.9	26	30
	6.0	600	18.3	4.34	72.4	26	30
	6.2	650	18.3	4.43	73.8	26	31
23 ° (44)	3.5	350	18.6	4.48	74.6	26	30
	4.0	400	18.9	4.76	79.4	27	31
	4.5	450	19.2	5.03	83.9	27	32
	5.0	500	19.5	5.29	88.1	28	32
	5.5	550	19.8	5.56	92.7	28	33
	6.0	600	20.1	5.79	96.5	29	33
	6.2	620	20.1	5.89	98.1	29	34
	6.5	650	20.1	6.01	100.2	30	34
	6.9	690	20.4	6.19	103.2	30	34
25 ° (45)	3.5	350	19.8	4.98	83.0	25	29
	4.0	400	20.1	5.33	88.7	26	30
	4.5	450	20.4	5.65	94.2	27	31
	5.0	500	20.7	5.96	99.3	28	32
	5.5	550	21.0	6.29	104.9	28	33
	6.0	600	21.0	6.57	109.6	30	34
	6.2	620	21.0	6.69	111.5	30	35

6.5	650	21.3	6.84	114.1	30	35
6.9	690	21.3	7.07	117.8	31	36

?:????????????180??????????360??????????2?

# I-40

??	??	??	??	??	?????MM/HR?		
	bar	kPa	m	m³/hr	l/min	■	▲
8 ° (40)	2.5	250	12.2	1.63	27.2	22	25
	3.0	300	12.5	1.80	30.0	23	27
	3.5	350	12.8	1.94	32.3	24	27
	4.0	400	12.8	2.06	34.4	25	29
	4.5	450	13.1	2.18	36.3	25	29
	5.0	500	13.4	2.29	38.2	25	29
	5.5	550	13.4	2.41	40.2	27	31
10 ° (41)	3.0	300	13.4	2.20	36.6	24	28
	3.5	350	13.7	2.37	39.4	25	29
	4.0	400	14.0	2.52	42.0	26	30
	4.5	450	14.0	2.67	44.5	27	31
	5.0	500	14.3	2.81	46.8	27	32
	5.5	550	14.6	2.96	49.3	28	32
	6.0	600	14.6	3.08	51.4	29	33
13 ° (42)	3.0	300	13.7	2.36	39.4	25	29
	3.5	350	14.0	2.55	42.6	26	30
	4.0	400	14.3	2.73	45.5	27	31
	4.5	450	14.3	2.90	48.3	28	33
	5.0	500	14.6	3.06	51.0	29	33
	5.5	550	14.9	3.23	53.9	29	33
	6.0	600	14.9	3.38	56.3	30	35
15 ° (43)	3.0	300	15.2	2.93	48.8	25	29
	3.5	350	15.5	3.19	53.2	26	30
	4.0	400	15.8	3.44	57.3	27	32
	4.5	450	15.8	3.67	61.2	29	34
	5.0	500	16.2	3.89	64.9	30	34
	5.5	550	16.5	4.14	68.9	31	35
	6.0	600	16.5	4.34	72.4	32	37
	6.2	620	16.5	4.43	73.8	33	38
23 ° (44)	3.5	350	16.8	4.48	74.6	32	37
	4.0	400	17.4	4.76	79.4	32	36
	4.5	450	17.7	5.03	83.9	32	37
	5.0	500	17.7	5.29	88.1	34	39
	5.5	550	18.0	5.56	92.7	34	40
	6.0	600	18.3	5.79	96.5	35	40
	6.2	620	18.6	5.89	98.1	34	39
	6.5	650	18.6	6.01	100.2	35	40
	6.9	690	18.6	6.19	103.2	36	41
25 ° (45)	3.5	350	17.4	4.98	83.0	33	38
	4.0	400	18.0	5.33	88.7	33	38
	4.5	450	18.3	5.65	94.2	34	39
	5.0	500	18.6	5.96	99.3	34	40
	5.5	550	18.9	6.29	104.9	35	41
	6.0	600	19.2	6.57	109.6	36	41

6.2	620	19.5	6.69	111.5	35	41
6.5	650	19.5	6.84	114.1	36	42
6.9	690	19.5	7.07	117.8	37	43

?:?????????????180??????????360?????????2?

# I-40

??	??	??	??	??	?????MM/HR?			
	bar	kPa	m	m <sup>3</sup> /hr	l/min	■	▲	
15 °	3.0	300	15.2	2.75	45.8	12	14	
	3.5	350	15.8	2.91	48.5	12	13	
	4.0	400	16.2	3.06	51.0	12	14	
	4.5	450	16.8	3.20	53.3	11	13	
	□	5.0	500	17.1	3.32	55.4	11	13
		5.5	550	17.4	3.46	57.7	11	13
		6.0	600	17.7	3.58	59.6	11	13
		6.2	620	17.7	3.62	60.4	12	13
18 °	3.0	300	17.4	2.90	48.3	10	11	
	3.5	350	17.7	3.15	52.5	10	12	
	4.0	400	18.0	3.38	56.4	10	12	
	4.5	450	18.0	3.61	60.1	11	13	
	□	5.0	500	18.3	3.82	63.7	11	13
		5.5	550	18.9	4.05	67.5	11	13
		6.0	600	19.2	4.25	70.8	12	13
		6.2	620	19.2	4.33	72.1	12	14
20 °	3.5	350	18.3	3.98	66.2	12	14	
	4.0	400	18.9	4.26	71.1	12	14	
	4.5	450	19.2	4.54	75.6	12	14	
	5.0	500	19.5	4.80	80.0	13	15	
	□	5.5	550	20.1	5.08	84.7	13	15
		6.0	600	19.8	5.32	88.7	14	16
		6.2	620	19.8	5.42	90.4	14	16
		6.5	650	20.1	5.55	92.5	14	16
23 °	6.9	690	20.1	5.74	95.7	14	16	
	3.5	350	18.9	4.23	70.6	12	14	
	4.0	400	19.5	4.55	75.8	12	14	
	4.5	450	19.8	4.85	80.8	12	14	
	5.0	500	20.1	5.14	85.6	13	15	
	□	5.5	550	20.4	5.45	90.8	13	15
		6.0	600	20.7	5.71	95.1	13	15
		6.2	620	20.7	5.82	97.0	14	16
25 °	6.5	650	20.7	5.96	99.4	14	16	
	6.9	690	21.0	6.17	102.9	14	16	
	3.5	350	19.5	4.60	76.7	12	14	
	4.0	400	20.1	4.92	82.1	12	14	
	4.5	450	20.4	5.23	87.2	13	14	
	5.0	500	20.7	5.52	92.0	13	15	
	□	5.5	550	21.0	5.84	97.3	13	15
		6.0	600	21.3	6.10	101.7	13	15
	6.2	620	21.3	6.22	103.6	14	16	
	6.5	650	21.3	6.36	106.0	14	16	
	6.9	690	21.6	6.57	109.5	14	16	

28°	3.5	350	19.8	5.73	95.5	15	17
	4.0	400	20.4	6.07	101.1	15	17
	4.5	450	21.0	6.38	106.4	14	17
	5.0	500	21.3	6.68	111.3	15	17
	5.5	550	21.9	7.00	116.7	15	17
	6.0	600	22.3	7.27	121.1	15	17
	6.2	620	22.3	7.38	122.9	15	17
	6.5	650	22.6	7.52	125.3	15	17
	6.9	690	23.2	7.73	128.8	14	17

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/cn/irrigation-product/chilunqudongxuanzhuanpentou/i-40>  
071424