

# Pro

Pro

- 
- 
- 
- 

- 2.1 bar 210 kPa
- Pro-Spray™ PRS30 2.1 bar 210 kPa
- 2

5

- 1.5 m
- ¼, ½,
- 0°







						mm/hr	
	bar	kPa	m	m³/hr	l/min	■	▲
90° Q	1.0	100	1.1	0.02	0.30	60	69
	1.5	150	1.3	0.02	0.38	54	62
	2.0	200	1.5	0.03	0.45	48	55
	2.1	210	1.5	0.03	0.46	49	57
	2.5	250	1.7	0.03	0.51	42	49
120° T	1.0	100					
	1.5	150					
	2.0	200	4A				
	2.1	210					
	2.5	250					
180° H	1.0	100	1.1	0.40	0.60	60	69
	1.5	150	1.3	0.05	0.76	54	62
	2.0	200	1.5	0.05	0.90	48	53
	2.1	210	1.5	0.06	0.92	49	57
	2.5	250	1.7	0.06	1.02	42	49
360° F	1.0	100	1.1	0.07	1.2	60	69
	1.5	150	1.3	0.09	1.52	54	62
	2.0	200	1.5	0.11	1.79	48	55
	2.1	210	1.5	0.11	1.85	49	57
	2.5	250	1.7	0.12	2.04	42	49

8

2.4 m

1/4, 1/3, 1/2, 1

0°





??	??	??	??	??	??	???	mm/hr
		bar	kPa	m	m <sup>3</sup> /hr	l/min	■ ▲
90° 	Q	1.0	100	1.7	0.04	0.62	51 59
		1.5	150	2.1	0.05	0.84	46 53
		2.0	200	2.4	0.06	1.00	42 48
		2.1	210	2.4	0.06	1.03	43 49
		2.5	250	2.7	0.07	1.13	37 43
120° 	T	1.0	100	1.7	0.05	0.83	51 59
		1.5	150	2.1	0.07	1.12	46 53
		2.0	200	2.4	0.08	1.33	42 48
		2.1	210	2.4	0.08	1.37	43 49
		2.5	250	2.7	0.09	1.51	37 33
180° 	H	1.0	100	1.7	0.08	1.33	55 64
		1.5	150	2.1	0.10	1.69	46 53
		2.0	200	2.4	0.12	1.99	42 48
		2.1	210	2.4	0.12	2.05	43 49
		2.5	250	2.7	0.14	2.27	37 43
360° 	F	1.0	100	1.7	0.16	2.67	55 64
		1.5	150	2.1	0.20	3.37	46 53
		2.0	200	2.4	0.24	3.99	42 48
		2.1	210	2.4	0.25	4.10	43 49
		2.5	250	2.7	0.27	4.54	37 43

10

3.0 m

1/4, 1/3, 1/2, 1

15°





??	??	??	??	??	??	????mm/hr	■	▲
	bar	kPa	m	m³/hr	l/min			
90° 	1.0	100	2.4	0.07	1.08	45	52	
	1.5	150	2.7	0.08	1.33	44	50	
	2.0	200	3.0	0.09	1.53	41	47	Q
	2.1	210	3.0	0.09	1.57	42	48	
	2.5	250	3.3	0.10	1.71	38	44	
120° 	1.0	100	2.4	0.09	1.44	45	52	
	1.5	150	2.7	0.11	1.77	44	50	
	2.0	200	3.0	0.12	2.04	41	47	T
	2.1	210	3.0	0.13	2.09	42	48	
	2.5	250	3.3	0.21	3.43	38	44	
180° 	1.0	100	2.4	0.13	2.17	45	52	
	1.5	150	2.7	0.16	2.65	44	50	
	2.0	200	3.0	0.18	3.06	41	47	H
	2.1	210	3.0	0.19	3.14	42	48	
	2.5	250	3.3	0.21	3.43	38	44	
360° 	1.0	100	2.4	0.26	4.33	45	52	
	1.5	150	2.7	0.32	5.31	44	50	
	2.0	200	3.0	0.37	6.13	41	47	F
	2.1	210	3.0	0.38	6.28	42	48	
	2.5	250	3.3	0.41	6.85	38	44	

12 

3.7 m

¼, ½, ¾, ⅜, ⅙

28°





??	??	??	??	??	??	????mm/hr	■	▲
	bar	kPa	m	m³/hr	l/min			
90° 	1.0	100	3.0	0.10	1.58	42	49	
	1.5	150	3.4	0.12	2.00	42	48	
	2.0	200	3.7	0.14	2.37	41	48	Q
	2.1	210	3.7	0.15	2.43	43	49	
	2.5	250	4.0	0.16	2.69	40	47	
120° 	1.0	100	3.0	0.13	2.11	42	49	
	1.5	150	3.4	0.16	2.67	42	48	
	2.0	200	3.7	0.19	3.16	41	48	T
	2.1	210	3.7	0.19	3.25	43	49	
	2.5	250	4.0	0.22	3.59	40	47	
180° 	1.0	100	3.0	0.19	3.17	42	49	
	1.5	150	3.4	0.24	4.01	42	48	
	2.0	200	3.7	0.28	4.73	41	48	H
	2.1	210	3.7	0.29	4.87	43	49	
	2.5	250	4.0	0.32	5.39	40	47	
360° 	1.0	100	3.0	0.38	6.33	42	49	
	1.5	150	3.4	0.48	8.01	42	48	
	2.0	200	3.7	0.57	9.47	41	48	F
	2.1	210	3.7	0.58	9.74	43	49	
	2.5	250	4.0	0.65	10.78	40	47	

15 

4.6 m

1/4, 1/3, 1/2, 2/3, 3/4, 1

28°





??	??	??	??	??	??	???	mm/hr
	bar	kPa	m	m <sup>3</sup> /hr	l/min	■	▲
90° 	1.0	100	3.9	0.15	2.50	39	46
	1.5	150	4.2	0.18	3.06	42	48
	2.0	200	4.6	0.21	3.54	40	46
	2.1	210	4.6	0.22	3.62	41	47
	2.5	250	4.9	0.24	3.95	40	46
120° 	1.0	100	3.9	0.20	3.33	39	46
	1.5	150	4.2	0.24	4.08	42	48
	2.0	200	4.6	0.28	4.71	40	46
	2.1	210	4.6	0.29	4.83	41	47
	2.5	250	4.9	0.32	5.27	40	46
180° 	1.0	100	3.9	0.30	5.00	39	46
	1.5	150	4.2	0.37	6.12	42	48
	2.0	200	4.6	0.42	7.07	40	46
	2.1	210	4.6	0.43	7.25	41	47
	2.5	250	4.9	0.47	7.91	40	46
360° 	1.0	100	3.9	0.60	10.00	39	46
	1.5	150	4.2	0.73	12.25	42	48
	2.0	200	4.6	0.85	14.14	40	46
	2.1	210	4.6	0.87	14.49	41	47
	2.5	250	4.9	0.95	15.81	40	46

17 

5.2 m

1/4, 1/2

28°

	??	??	??	??	??	???	???	mm/hr
	bar	kPa	m	m <sup>3</sup> /hr	l/min	■	▲	
90° 	1.0	100	4.7	0.19	3.17	34	40	
	1.5	150	4.9	0.23	3.88	39	45	
	2.0	200	5.2	0.27	4.48	40	46	
	2.1	210	5.2	0.28	4.59	41	47	
	2.5	250	5.5	0.30	5.01	40	46	
120° 	1.0	100						
	1.5	150						
	2.0	200				□□□ 17A □		
	2.1	210						
	2.5	250						
180° 	1.0	100	4.7	0.38	6.33	34	40	
	1.5	150	4.9	0.47	7.76	39	45	
	2.0	200	5.2	0.54	8.96	40	46	
	2.1	210	5.2	0.55	9.18	41	47	
	2.5	250	5.5	0.60	10.01	40	46	
360° 	1.0	100						
	1.5	150						
	2.0	200				□□□ 17A □		
	2.1	210						
	2.5	250						

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/cn/irrigation-product/penzui/pro-gudingjiaodupenzui>

071724