Hunter® | Built on Innovation®

# 水泵启动继电器

这种可靠且经济的水泵启动继电器系列非常适合需要泵激活的系统。


Pump Start Relay
Single Phase
Coil VA Inrush
VA Holding
5 HP@110VAC
7.5 HP@240VAC
Maximum Resistive Amps 50
56
6
Power In (Line)
Power (Load)
Ground (Line)
Ground (Load)
P/MV (Red)
Common (White)
(24VAC wire connections made in junction box)
DANGER/PELIGRO
HAZARDOUS VOLTAGE/TENSION PELIGROSA
Hunter

## 主要优势

- 满足各种电压和功率要求的水泵启动继电器系列
- 24 VAC 预留接线可快速轻松地连接到控制器
- 适用于传统接线或两线解码器激活
- 为电源不足的水泵启动继电器安装提供解决方案激活水泵
- 包括固态继电器和本地 24 VAC 变压器，用于简单的 PSR 激活

## 运行参数

- 建议安装: 距离灌溉控制器至少 4.5 米
- 主交流电源输入: 120/230 VAC,
- 次交流电源输出: 24 VAC, 1.6 A
- 继电器额定值: 双极、双掷固态 (10 A)
- 认证: IP54 ,UL ,CE ,NEMA 3R 等级
- 质保期: 2 年

水泵启动继电器电气参数

| 型号 | 单相 | | 3相 | 最大满载 (安培) | 最大阻性 (安培) | 凉爽 VA | | 凉爽 VA | |
|---|---|---|---|---|---|---|---|---|---|
| | **kW at 120 VAC** | **kW at 230 VAC** | **kW at 230 VAC** | | | 启动 | (安培) | 保持 | **(Amps)** |
| PSR-22 | 1.5* | 2.2* | N/A | 30 | 40 | 33 | (1.38) | 8 | (0.33) |
| PSR-52 | 2.2 | 5.6 | N/A | 40 | 50 | 65 | (2.71) | 7.5 | (0.31) |
| PSR-53 | 2.2 | 5.6 | 7.5 | 40 | 50 | 65 | (2.71) | 7.5 | (0.31) |

注: *大约功率

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

https://www.hunterindustries.com/cn/irrigation-product/kongzhiqi/shuibengqidongjidianqi
071624