

STK-5B / STK-6B

A Unique Package of Irrigation Products Designed To Cool and Clean Synthetic Turf Sports Fields

KEY BENEFITS

- Nozzle choices: 6
- Standard nozzle: #20
- Nozzle range: #16 to #26
- Nozzle trajectory: 22.5 degrees
- Gear-drive: Isolated, grease lubricated
- Factory installed rubber logo cap (ST-1600B)
- Arc Adjustment: Movable stops left & right
- Arc setting: 40° to non-reversing 360°
- Ratcheting nozzle turret
- Telescoping rubber infill barrier on riser
- Adjustable speed of rotation: 0 to 80 seconds (180° @ 8 bar)
- 5-year component part warranty
- Internal construction: Brass, stainless steel & ball-bearings



Operating Specifications

- Radius: 32.5 to 50.3 m
- Flow rate: 21.8 to 74.2 m³/hr; 364 to 1,237 l/min
- Operating pressure range: 4.0 to 8.0 bars; 400 to 800 kPa
- Precipitation rate: 60 mm/hr approx.

ST-1600 NOZZLE PERFORMANCE DATA

Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
16	4.0	400	32.5	21.8	364	41.4	47.8
	5.0	500	35.0	24.4	406	39.8	45.9
	6.0	600	37.0	26.8	446	39.1	45.1
	7.0	700	39.0	28.9	482	38.0	43.9
	8.0	800	41.0	31.2	520	37.1	42.9
18	4.0	400	34.0	24.3	405	42.0	48.6
	5.0	500	37.0	27.1	452	39.6	45.8
	6.0	600	39.0	29.8	496	39.1	45.2
	7.0	700	40.5	32.1	535	39.1	45.2
	8.0	800	43.0	34.8	580	37.6	43.5
20	4.0	400	35.0	32.7	545	53.4	61.7
	5.0	500	39.0	36.5	609	48.1	55.5
	6.0	600	43.0	40.1	668	43.4	50.1
	7.0	700	44.0	43.3	721	44.7	51.6
	8.0	800	45.0	46.4	773	45.8	52.9
22	4.0	400	36.0	38.9	649	60.1	69.4
	5.0	500	39.5	43.6	726	55.8	64.5
	6.0	600	44.0	47.7	795	49.3	56.9
	7.0	700	47.0	51.5	859	46.7	53.9
	8.0	800	48.0	55.2	920	47.9	55.3
24	4.0	400	37.0	45.9	765	67.1	77.4
	5.0	500	40.5	51.3	855	62.6	72.2
	6.0	600	45.0	56.2	937	55.5	64.1
	7.0	700	47.5	60.7	1012	53.8	62.2
	8.0	800	48.7	65.0	1084	54.9	63.3
26	4.0	400	38.4	53.0	883	71.8	82.9
	5.0	500	41.4	59.2	986	68.8	79.5
	6.0	600	46.0	64.6	1077	61.0	70.4
	7.0	700	48.7	69.7	1162	58.6	67.7
	8.0	800	50.3	74.2	1237	58.7	67.8

Note: All precipitation rates calculated for 180 degree operation. For precipitation rate of 360 degree sprinkler divide by 2.



ST-243642B

4-Piece Cover Set	61 x 91 x 7.6 cm
Exposed Rim	67 x 97 cm
Overall Height	107 cm
Base Pad	112 x 127 cm
	* Not for use with ST-1600BR Rotor

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/en-metric/irrigation-product/discontinued-models/stk-5b-stk-6b>
071724