

## G-995

Covering 20.1 to 29.6 m, the G-995 is the perfect combination of performance and reliability.

### KEY BENEFITS

- Adjustable arc water lubricated gear-drive
- 40 to 360 degree adjustable arc range
- Arc can be adjusted anytime; uninstalled, installed or while in operation
- Quick check arc mechanism makes arc adjust fast and easy
- Exclusive PressurePort™ technology delivers uniform and consistent coverage
- Closed-case design helps prevent sticking riser and leaking seals
- Flexible performance with 16 nozzles to choose from



### MODEL SPECIFICATIONS

- Adjustable Arc (40° to 360°)

### MODEL VARIATIONS

- **C** = Check-O-Matic checks up to 8 m in elevation change and readily converts to Normally Open Hydraulic with through the top connections
- **D** = Decoder Valve-In-Head with all "E" specifications below
- **DD** = 2-Station Decoder Valve-In-Head with all "E" specifications below
- **E** = Electric Valve-In-Head with adjustable pressure regulation, on-off-auto selector, 210mA (370mA inrush) solenoid with captive plunger and internal downstream bleed.

### OPERATING SPECIFICATIONS

- Discharge rate: 6.7 - 19.04 m<sup>3</sup>/hr, 111.7 - 317.2 l/min
- Radius: 20.1 - 29.6 m
- Pressure range: 5.5 - 8.3 Bar, 551 - 827 kPa
- Pressure rating: 1000 kPa



**G995**

Overall Height	34 cm
Pop-up Height	8 cm
Flange Diameter	19 cm
Inlet Size	1-1/2" Female ACME

## G995 NOZZLE PERFORMANCE DATA\*

Nozzle	Pressure		Radius	Flow		Precip mm/hr	
	bar	kPa		m	m <sup>3</sup> /hr	l/min	■
25 • Lt. Blue	5.5	550	20.1	6.70	111.7	16.6	19.1
	6.2	620	20.4	7.16	119.2	17.2	19.8
	6.9	690	20.7	7.54	125.7	17.6	20.3
	7.6	760	21.0	8.09	134.8	18.3	21.1
	8.3	830	21.0	8.52	142.0	19.3	22.2
33 • Grey	5.5	550	20.7	8.22	137.0	19.1	22.1
	6.2	620	21.0	8.68	144.6	19.6	22.7
	6.9	690	21.3	9.18	152.9	20.2	23.3
	7.6	760	21.6	9.68	161.3	20.7	23.9
	8.3	830	21.9	10.18	169.6	21.1	24.4
38 • Red	5.5	550	21.9	9.22	153.7	19.1	22.1
	6.2	620	22.3	9.77	162.8	19.7	22.8
	6.9	690	22.9	10.31	171.9	19.7	22.8
	7.6	760	23.2	10.81	180.2	20.1	23.3
	8.3	830	23.5	11.36	189.3	20.6	23.8
43 • Dk. Brown	5.5	550	22.6	10.47	174.5	20.6	23.8
	6.2	620	22.6	11.02	183.6	21.7	25.0
	6.9	690	22.9	11.52	191.9	22.0	25.4
	7.6	760	23.5	12.13	202.1	22.0	25.4
	8.3	830	23.8	12.65	210.8	22.4	25.8
48 • Dk. Green	5.5	550	23.5	11.40	190.0	20.7	23.9
	6.2	620	24.1	11.95	199.1	20.6	23.8
	6.9	690	24.7	12.52	208.6	20.5	23.7
	7.6	760	25.0	13.06	217.7	20.9	24.1
	8.3	830	25.3	13.74	229.0	21.5	24.8
53 • Dk. Blue	5.5	550	24.7	12.47	207.8	20.5	23.6
	6.2	620	25.6	12.99	216.5	19.8	22.9
	6.9	690	26.2	13.52	225.2	19.7	22.7
	7.6	760	26.5	14.11	235.1	20.1	23.2
	8.3	830	26.8	14.63	243.8	20.3	23.5
63 • Black	5.5	550	26.2	14.15	235.8	20.6	23.8
	6.2	620	26.8	14.88	247.9	20.7	23.9
	6.9	690	27.4	15.67	261.2	20.8	24.0
	7.6	760	27.7	16.33	272.2	21.2	24.5
	8.3	830	28.0	16.97	282.8	21.6	24.9
73 • Orange	5.5	550	27.1	16.51	275.2	22.4	25.9
	6.2	620	27.7	17.13	285.4	22.3	25.7
	6.9	690	28.3	17.74	295.6	22.1	25.5
	7.6	760	29.0	18.38	306.2	21.9	25.3
	8.3	830	29.6	19.04	317.2	21.8	25.1

**Note:** \*Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral.

\*\* For low angle nozzle performance, reduce radius by 15%

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/en-metric/irrigation-product/golf-rotors/g-995>  
071724