

Eco-Wrap

Irrigate more efficiently than blank dripline with fleece-wrapped dripline.

KEY BENEFITS

- Perfect for narrow areas that are difficult to irrigate with standard methods
- Anti-siphon feature and fleece wrap protect against debris and root intrusion
- Saves 20–40% more water than standard products due to superior capillary movement of water to the entire root zone, promoting healthier root growth
- Non-draining, pressure-compensating emitters open/close simultaneously, maximising efficiency
- Check height of 1.5 m minimises system drainage and runoff



Operating Specifications

- Operating range: 1.0 to 3.5 bar; 100 to 350 kPa
- Minimum filtration: 120 mesh; 125 microns
- Air relief recommended for sloping conditions greater than 1.5 m
- Recommended installation depth: turf (10–16 cm); other (10–30 cm)
- Compatible with Eco-Mat
- Warranty period: 5 years (plus 2 additional years for environmental stress cracking)

Product Specifications

- Flow rate: 2.1 l/hr
- Emitter spacing: 30 cm
- Tubing dimensions: 0.660" x 0.560" (outside/inside diameter)
- Roll length: 16 mm = 100 m; 17 mm = 90 m
- Accepts 16 mm barb or LOC fittings

ECO-WRAP TECHNICAL SPECIFICATIONS

	16mm	17mm
Flow	2.2 l/hr; 0.13 m ³ /hr	2.2 l/hr; 0.13 m ³ /hr
Roll Length	100 m	76 m
Operating Pressure	1.0 to 3.5 bar; 100 to 350 kPa	1.0 to 3.5 bar; 100 to 350 kPa
Minimum Filtration	120 mesh	120 mesh
Emitter Spacing	30 cm	30 cm

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.