

GT-884

These rotors have Total-Top-Serviceability, powerful G-800 Series gear drives, and the largest flange compartment in the industry to accommodate all two-way module components.

KEY BENEFITS

- Adjustable model distinguished by a gray collar that comes factory set in a true full-circle configuration
- Extra-large, fast access flange compartment to accommodate full-size DBRY-6 Splice Connectors and an integrated PilotTwo-Way Module
- Solenoid and pressure regulator are serviceable without system depressurization
- Exclusive PressurePort™ Nozzle Technology optimizes incoming pressure at each nozzle to increase consistency and maximize distribution uniformity
- High-torque gear drive is the strongest in the industry to mitigate the challenges of debris infiltration
- Proprietary Filter Sentry™ Mechanism cleans the filter with every opening and closing cycle



OPERATING SPECIFICATIONS

















- Radius: 14.9 to 29.6 m
- Flow: 3.23 to 13.29 m³/hr; 53.8 to 221.4 l/min
- Pressure range: 3.4 to 6.9 bar; 340 to 690 kPa
- All TTS rotors are pressure rated at 10 bar; 1,000 kPa



OPTIONS

- **C** - Check-O-Matic checks up to 8 m in elevation change and readily converts to Normally Open Hydraulic with through the top connections
- **D** - Decoder Valve-in-Head with all "E" specifications below*
- **DD** - Two-station Decoder Valve-in-Head with all "E" specifications below*
- **E** - Electric Valve-in-Head with adjustable pressure regulation, on-off-auto selector, 210 mA (370 mA inrush) 50 Hz; 190 mA (350 mA inrush) 60 Hz solenoid with captive plunger and internal downstream bleed

*All DIH rotors include two 3M DBRY-6 splices for connection to the two-wire path.

TTS-884 / G884 / G84B NOZZLE PERFORMANCE DATA* - METRIC

| Nozzle | | | Pressure | | Radius | Flow | | Precip mm/hr | |
|------------------------------------------------------------------------------------------------------------|-------------------|-----------------------------------------------------------------------------------------------------------|----------|-----|--------|--------------------|-------|--------------|------|
| | | | bar | kPa | m | m ³ /hr | l/min | ■ | ▲ |
| Tan  803611 | 15 ° White | Gray  315317 | 3.4 | 344 | 14.9 | 3.23 | 53.8 | 14.5 | 16.7 |
| | | | 4.1 | 413 | 15.5 | 3.57 | 59.4 | 14.8 | 17.0 |
| | | | 4.5 | 450 | 15.9 | 3.73 | 62.1 | 14.8 | 17.1 |
| | | | 4.8 | 482 | 16.2 | 3.86 | 64.4 | 14.8 | 17.1 |
| | | | 5.5 | 551 | 16.8 | 4.13 | 68.9 | 14.7 | 17.0 |
| Tan  803611 | 18 ° Orange | Gray  315317 | 3.4 | 344 | 17.1 | 3.91 | 65.1 | 13.4 | 15.5 |
| | | | 4.1 | 413 | 17.7 | 4.28 | 71.3 | 13.7 | 15.8 |
| | | | 4.5 | 450 | 18.0 | 4.48 | 74.6 | 13.8 | 16.0 |
| | | | 4.8 | 482 | 18.3 | 4.54 | 75.7 | 13.6 | 15.7 |
| | | | 5.5 | 551 | 18.6 | 4.82 | 80.3 | 13.9 | 16.1 |
| Tan  803611 | 20 ° Brown | Gray  3153147 | 3.4 | 344 | 17.4 | 4.18 | 69.7 | 13.8 | 16.0 |
| | | | 4.1 | 413 | 18.0 | 4.61 | 76.8 | 14.3 | 16.5 |
| | | | 4.5 | 450 | 18.6 | 4.86 | 81.0 | 14.1 | 16.2 |
| | | | 4.8 | 482 | 19.2 | 4.91 | 81.8 | 13.3 | 15.4 |
| | | | 5.5 | 551 | 19.5 | 5.16 | 85.9 | 13.5 | 15.6 |
| Tan  803611 | 23 ° Green | Lt. Blue  315311 | 3.4 | 344 | 19.2 | 4.91 | 81.8 | 13.3 | 15.4 |
| | | | 4.1 | 413 | 19.8 | 5.22 | 87.1 | 13.3 | 15.4 |
| | | | 4.5 | 450 | 20.1 | 5.45 | 90.8 | 13.5 | 15.6 |
| | | | 4.8 | 482 | 20.4 | 5.66 | 94.3 | 13.6 | 15.7 |
| | | | 5.5 | 551 | 20.7 | 6.04 | 100.7 | 14.1 | 16.2 |
| Tan  803611 | 25 ° Blue | Lt. Blue  315311 | 4.5 | 450 | 21.6 | 6.50 | 108.3 | 13.9 | 16.0 |
| | | | 4.8 | 482 | 22.3 | 6.75 | 112.5 | 13.6 | 15.7 |
| | | | 5.5 | 551 | 22.6 | 7.19 | 119.8 | 14.1 | 16.3 |
| | | | 6.2 | 620 | 22.9 | 7.65 | 127.5 | 14.6 | 16.9 |
| | | | 6.9 | 689 | 23.5 | 8.12 | 135.3 | 14.7 | 17.0 |
| Tan  803611 | 33 ° Grey | Lt. Blue  315311 | 4.5 | 450 | 22.6 | 7.02 | 117.0 | 13.8 | 15.9 |
| | | | 4.8 | 482 | 22.9 | 7.27 | 121.1 | 13.9 | 16.1 |
| | | | 5.5 | 551 | 23.5 | 7.77 | 129.5 | 14.1 | 16.3 |
| | | | 6.2 | 620 | 24.1 | 8.22 | 137.0 | 14.2 | 16.4 |
| | | | 6.9 | 689 | 24.7 | 8.68 | 144.6 | 14.2 | 16.4 |
| Tan  803611 | 38 ° Red | Lt. Blue  315311 | 4.5 | 450 | 23.5 | 7.97 | 132.9 | 14.5 | 16.7 |
| | | | 4.8 | 482 | 24.1 | 8.31 | 138.5 | 14.3 | 16.6 |
| | | | 5.5 | 551 | 25.0 | 8.84 | 147.3 | 14.1 | 16.3 |
| | | | 6.2 | 620 | 25.6 | 9.38 | 156.3 | 14.3 | 16.5 |
| | | | 6.9 | 689 | 26.5 | 9.90 | 165.0 | 14.1 | 16.3 |
| Tan  803611 | 43 ° Dk. Brown | Blue  315311 | - | - | - | - | - | - | - |
| | | | 4.8 | 482 | 25.3 | 9.38 | 156.3 | 14.7 | 16.9 |
| | | | 5.5 | 551 | 25.9 | 9.90 | 165.0 | 14.8 | 17.0 |
| | | | 6.2 | 620 | 26.5 | 10.52 | 175.3 | 15.0 | 17.3 |
| | | | 6.9 | 689 | 27.1 | 11.09 | 184.7 | 15.1 | 17.4 |
| Dk. Brown  803610 | 48 ° Dk. Green | Dk. Blue  833500 | - | - | - | - | - | - | - |
| | | | 4.8 | 482 | 27.4 | 10.65 | 177.5 | 14.2 | 16.3 |
| | | | 5.5 | 551 | 28.0 | 11.11 | 185.1 | 14.1 | 16.3 |
| | | | 6.2 | 620 | 28.7 | 11.46 | 191.0 | 14.0 | 16.1 |

| 6.9 | 689 | 29.3 | 12.15 | 202.5 | 14.2 | 16.4 | | | |
|---------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------------------------------------------------------------------------------------------|-------|-------|------|-------|-------|------|------|
| Dk. Brown  803610 | 53 • Dk. Blue | Dk. Blue  833500 | - | - | - | - | - | - | - |
| | | | 4.8 | 482 | 27.7 | 11.31 | 188.5 | 14.7 | 17.0 |
| | | | 5.5 | 551 | 28.3 | 11.86 | 197.7 | 14.8 | 17.0 |
| | | | 6.2 | 620 | 29.0 | 12.61 | 210.1 | 15.0 | 17.4 |
| | | | 6.9 | 689 | 29.6 | 13.29 | 221.4 | 15.2 | 17.6 |
| Note: Nozzle plug P/N 315300 installed in the front side of the nozzle housing. * Preliminary performance data. | | | | | | | | | |

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/en-metric/irrigation-product/golf-rotors/gt-884>
 071724