

## I-90

The robust I-90 Rotor is built for long-distance natural turf applications in large parks, open spaces, and sports fields.

### KLUCZOWE KORZYŚCI

- Exclusive PressurePort™ Technology creates exceptional nozzle uniformity
- Forward-facing triple nozzles (I-90), opposing triple nozzles (I-90-ON) create uniform nozzle profiles in part- and full-circle applications
- QuickCheck™ Arc Mechanism for fast arc adjustment and review of the arc setting
- Part- and full-circle in one model provides flexible installation options and decreases inventory (I-90)
- Drain Check Valve prevents low-head drainage (up to 2 meters of elevation)

### Operating Specifications

- I-90 nozzle choices: 8
- Radius I-90 ADV: 20.1 to 29.6 m
- Radius I-90 36V: 22.3 to 31.4 m
- Flow I-90 ADV: 6.7 to 19.04 m<sup>3</sup>/hr; 111.7 l/min
- Flow I-90 36V: 6.93 to 18.92 m<sup>3</sup>/hr; 115.5 to 315.3 l/min
- Recommended pressure range: 5.5 to 8.3 bar; 550 to 830 kPa
- Operating pressure range: 5.5 to 8.3 bar; 550 to 1030 kPa
- Precipitation rate: 19 mm/hr approximately
- Warranty period: 5 years

### Factory-Installed Options

- Reclaimed water ID

### User-Installed Options

- [Prefabricated PVC HSJ Swing Joints](#)
- Rubber Cover Kit P/N 959300SP
- Rubber Cover Kit P/N 234200
- Sod Cup Kit P/N 467955
  - No-dig servicing
  - No-dig arc adjustments
  - Quick-release turf cup assembly
  - Threads in cup lock/retain the turf



## WYDAJNOSC DYSZY I-90-ADV - DANE

Dysza	Cisnienie		Pronien	Przepływ		Opad mm/hr	
	bar	kPa		m	m <sup>3</sup> /hr	l/min	■
25 ° Jasno Niebieski	5,5	550	20,1	6,70	111,7	33,1	38,2
	6,0	600	20,4	7,16	119,2	34,3	39,6
	7,0	700	20,7	7,54	125,7	35,1	40,5
	7,5	750	21,0	8,09	134,8	36,6	42,2
33 ° Szary	5,5	550	20,7	8,22	137,0	38,3	44,2
	6,0	600	21,0	8,68	144,6	39,2	45,3
	7,0	700	21,3	9,18	152,9	40,3	46,6
	7,5	750	21,6	9,68	161,3	41,3	47,7
38 ° Czerwony	5,5	550	21,9	9,22	153,7	38,3	44,2
	6,0	600	22,3	9,77	162,8	39,5	45,6
	7,0	700	22,9	10,31	171,9	39,5	45,6
	7,5	750	23,2	10,81	180,2	40,3	46,5
43 ° Ciemno Brazowy	5,5	550	22,6	10,47	174,5	41,2	47,5
	6,0	600	22,6	11,02	183,6	43,3	50,0
	7,0	700	22,9	11,52	191,9	44,1	50,9
	7,5	750	23,5	12,13	202,1	44,0	50,9
48 ° Ciemno Zielony	5,5	550	23,5	11,40	190,0	41,4	47,8
	6,0	600	24,1	11,95	199,1	41,2	47,6
	7,0	700	24,7	12,52	208,6	41,1	47,4
	7,5	750	25,0	13,06	217,7	41,8	48,3
53 ° Ciemnoniebieski *	5,5	550	24,7	12,47	207,8	40,9	47,2
	6,0	600	25,6	12,99	216,5	39,6	45,8
	7,0	700	26,2	13,52	225,2	39,3	45,4
	7,5	750	26,5	14,11	235,1	40,1	46,3
	8,0	800	26,8	14,63	243,8	40,7	47,0
63 ° Czarny	5,5	550	26,2	14,15	235,8	41,2	47,6
	6,0	600	26,8	14,88	247,9	41,4	47,8
	7,0	700	27,4	15,67	261,2	41,7	48,1
	7,5	750	27,7	16,33	272,2	42,5	49,0
	8,0	800	28,0	16,97	282,8	43,2	49,8
73 ° Pomarańczowy	5,5	550	27,1	16,51	275,2	44,9	51,8
	6,0	600	27,7	17,13	285,4	44,5	51,4
	7,0	700	28,3	17,74	295,6	44,2	51,0
	7,5	750	29,0	18,38	306,2	43,8	50,6
	8,0	800	29,6	19,04	317,2	43,5	50,3

\* Dysza instalowana fabrycznie

**Uwaga:**

Wszystkie wskaźniki opadów dla modeli ADV obliczono przy pracy dyszy w zakresie 180 stopni. W przypadku opadu dla zraszaczy pracujących w zakresie 360 stopni wartość wskaźnika należy podzielić przez 2. Wskaźniki opadów dla modelu 36V obliczono przy pracy dyszy w zakresie 360 stopni.

## WYDAJNOSC DYSZY I-90-36V - DANE

Dysza	Cisnienie		Pronien	Przepływ		Opad mm/hr	
	bar	kPa		m	m <sup>3</sup> /hr	l/min	■
25 • Jasno Niebieski	5,5	550	22,3	6,93	115,5	14,0	16,2
	6,0	600	22,9	7,36	122,6	14,1	16,3
	7,0	700	23,2	7,79	129,8	14,5	16,8
	7,5	750	23,8	8,29	138,2	14,7	16,9
33 • Szary	5,5	550	23,5	8,25	137,4	15,0	17,3
	6,0	600	23,8	8,72	145,4	15,4	17,8
	7,0	700	24,4	9,22	153,7	15,5	17,9
	7,5	750	24,7	9,70	161,6	15,9	18,4
38 • Czerwony	5,5	550	24,4	9,22	153,7	15,5	17,9
	6,0	600	25,0	9,75	162,4	15,6	18,0
	7,0	700	25,3	10,29	171,5	16,1	18,6
	7,5	750	25,9	10,84	180,6	16,1	18,6
43 • Ciemno Brazowy	5,5	550	25,3	10,49	174,9	16,4	18,9
	6,0	600	25,6	11,04	184,0	16,8	19,4
	7,0	700	25,9	11,56	192,7	17,2	19,9
	7,5	750	26,2	12,13	202,1	17,7	20,4
48 • Ciemno Zielony	5,5	550	26,2	11,27	187,8	16,4	18,9
	6,0	600	27,1	11,93	198,7	16,2	18,7
	7,0	700	27,4	12,45	207,4	16,5	19,1
	7,5	750	27,7	13,02	216,9	16,9	19,5
53 • Ciemnoniebieski *	5,5	550	27,1	12,31	205,2	16,7	19,3
	6,0	600	27,4	12,88	214,6	17,1	19,8
	7,0	700	28,0	13,45	224,1	17,1	19,7
	7,5	750	28,3	14,02	233,6	17,4	20,1
	8,0	800	28,7	14,58	243,0	17,8	20,5
63 • Czarny	5,5	550	28,0	14,36	239,2	18,3	21,1
	6,0	600	28,7	14,97	249,5	18,2	21,1
	7,0	700	29,3	15,76	262,7	18,4	21,3
	7,5	750	29,6	16,36	272,5	18,7	21,6
	8,0	800	29,9	17,01	283,5	19,1	22,0
73 • Pomarańczowy	5,5	550	29,3	16,38	272,9	19,1	22,1
	6,0	600	29,9	17,04	283,9	19,1	22,0
	7,0	700	30,2	17,67	294,5	19,4	22,4
	7,5	750	31,1	18,29	304,7	18,9	21,8
	8,0	800	31,4	18,92	315,3	19,2	22,2

\* Dysza instalowana fabrycznie

**Uwaga:**

Wszystkie wskaźniki opadów dla modeli ADV obliczono przy pracy dyszy w zakresie 180 stopni. W przypadku opadu dla zraszaczy pracujących w zakresie 360 stopni wartość wskaźnika należy podzielić przez 2. Wskaźniki opadów dla modelu 36V obliczono przy pracy dyszy w zakresie 360 stopni.

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/pl/irrigation-product/rotory/i-90>  
071724