

# Solenoids

Heavy-duty Hunter 24 VAC or latching solenoids provides dependable operation and long life performance.

## KEY BENEFITS

- Compatible with all Hunter irrigation valves
- Energy-efficient, low-power design
- Engineered with ultra-durable, heavy-duty materials for maximum longevity
- Stops water intrusion and protects critical electrical components
- Pre-wired with 18" of valve-control wire
- Captive plunger offers easy servicing of solenoid
- Manual quarter-turn on/off control
- Easy installation with no tools required


## ELECTRICAL SPECIFICATIONS

### 606800

- Minimum opening/operating voltage: 19 VAC
- Maximum recommended voltage: 28 VAC
- Current at 24 VAC:
  - 350 mA inrush, 190 mA holding, 60 Hz
  - 370 mA inrush, 210 mA holding, 50 Hz
- Maximum operating pressure: 220 PSI
- Wire leads: 18' of 18 AWG UL-approved wire

### 458200

- Minimum opening/operating voltage: 6 VDC
- Maximum recommended voltage: 9 VDC
- Coil resistance: 4.8 ohms nominal
- Maximum operating pressure: 200 PSI
- Wire leads: 18' of 18 AWG black and red UL-approved wire



Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/irrigation-product/accessories/solenoids>  
071724