

## PGJ

The highly durable PGJ offers all the benefits of a large rotor in a compact, spray-sized package, with water-efficient nozzles and easy arc adjustment.

### KEY BENEFITS

- Headed and slotted setscrew allows radius adjustment with a Hunter Wrench or flat-blade screwdriver
- Adjustable arc from 40° to 360° to keep water in the appropriate areas
- Standard factory-installed 2.0 nozzle speeds installation
- QuickCheck™ Arc Mechanism for fast arc adjustment

### Operating Specifications

- Nozzle choices: 8
- Radius: 15' to 34'
- Flow: 0.42 to 4.3 GPM
- Recommended pressure range: 30 to 50 PSI
- Operating pressure range: 20 to 100 PSI
- Precipitation rate: 0.6 in/hr approximately
- Nozzle trajectory: 14° approximately
- Warranty period: 2 years

### Factory-Installed Options

- Drain Check Valve (up to 7' of elevation) excluding PGJ-00
- Reclaimed water ID

### User-Installed Options

- Drain Check Valve (up to 7' of elevation) excluding PGJ-00 (P/N 462078SP)
- HC-50F-50M Check Valve (up to 32' of elevation)



PGJ NOZZLE PERFORMANCE DATA					
Nozzle	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM	■	▲
.75 • Red	30	15	0.64	0.55	0.63
	<b>40</b>	<b>16</b>	<b>0.75</b>	<b>0.56</b>	<b>0.65</b>
	50	17	0.85	0.57	0.65
1.0 • Red	30	18	0.85	0.51	0.58
	<b>40</b>	<b>19</b>	<b>1.0</b>	<b>0.53</b>	<b>0.62</b>
	50	19	1.1	0.59	0.68
1.5 • Red	30	21	1.3	0.57	0.66
	<b>40</b>	<b>22</b>	<b>1.5</b>	<b>0.60</b>	<b>0.69</b>
	50	22	1.7	0.68	0.78
2.0 • Red	30	24	1.7	0.57	0.66
	<b>40</b>	<b>25</b>	<b>2.0</b>	<b>0.62</b>	<b>0.71</b>
	50	25	2.3	0.71	0.82
2.5 • Red	30	27	2.2	0.58	0.67
	<b>40</b>	<b>28</b>	<b>2.5</b>	<b>0.61</b>	<b>0.71</b>
	50	28	2.8	0.69	0.79
3.0 • Red	30	30	2.5	0.53	0.62
	<b>40</b>	<b>31</b>	<b>3.0</b>	<b>0.60</b>	<b>0.69</b>
	50	31	3.4	0.68	0.79
4.0 • Red	30	33	3.7	0.65	0.76
	<b>40</b>	<b>34</b>	<b>4.0</b>	<b>0.67</b>	<b>0.77</b>
	50	34	4.3	0.72	0.83
5.0 • Red	30	36	4.7	0.70	0.81
	<b>40</b>	<b>37</b>	<b>5.0</b>	<b>0.70</b>	<b>0.81</b>
	50	37	5.3	0.75	0.86

**Notes:**

**Bold** = Recommended pressure.

All precipitation rates calculated for 180 degree operation. For the precipitation rate for a 360 degree sprinkler, divide by 2.

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/irrigation-product/rotors/pgj>  
071424