

Pro-HC

Use this rugged, professional-grade Wi-Fi controller for residential and light commercial applications.

KEY BENEFITS

- Number of stations: 6, 12, or 24
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- Advanced programming option provides station-based programming with up to 6 total start times available
- Includes 4' (1.2m) lead and plug
- 2 sensor inputs available for use with any Klik Sensor and HC Flow Meter
- 1 P/MV output for pump start relay and master valve activation
- Wi-Fi enabled for quick connection to Hydrawise Software
- 2¾" full-color touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts



OPERATING SPECIFICATIONS

- Transformer input: 120 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- 2.4 GHz (only) Wi-Fi router compatible, 802.11 b/g/n 20 MHz
- Supported security protocols: WPA/WPA2 Personal and Enterprise, TLS
- Approvals: Plastic IP44, UL, cUL, FCC, CE, UKCA RCM
- Warranty period: 2 years

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/irrigation-product/controllers/pro-hc>
063024