

I-90

The robust I-90 Rotor is built for long-distance natural turf applications in large parks, open spaces, and sports fields.

KEY BENEFITS

- Exclusive PressurePort™ Technology creates exceptional nozzle uniformity
- Forward-facing triple nozzles (I-90) or opposing triple nozzles (I-90-ON) create uniform nozzle profiles in part- and full-circle applications
- QuickCheck™ Arc Mechanism for fast arc adjustment and review of the arc setting
- Part- and full-circle in one model provides flexible installation options and decreases inventory (I-90)
- Drain Check Valve prevents low-head drainage (up to 7' of elevation)

Operating Specifications

- Nozzle trajectory: 22.5°
- I-90 nozzle choices: 8
- Radius I-90 ADV: 66' to 97'
- Radius I-90 36V: 73' to 103'
- Flow I-90 ADV: 29.5 to 83.8 GPM
- Flow I-90 36V: 30.5 to 83.3 GPM
- Recommended pressure range: 80 to 120 PSI
- Operating pressure range: 80 to 120 PSI
- Precipitation rate: 0.75 in/hr approximately
- Warranty period: 5 years

Factory-Installed Options

- Reclaimed water ID

User-Installed Options

- [Prefabricated PVC HSJ Swing Joints](#)
- Upper Snap Ring Assembly P/N 450105
- Rubber Cover Kit P/N 959300SP
- Turf Cup Kit P/N 959400SP
 - No-dig servicing
 - No-dig arc adjustments
 - Quick-release turf cup assembly
 - Threads in cup lock/retain the turf



I-90-ADV NOZZLE PERFORMANCE DATA

Nozzle	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM	■	▲
25 * Lt. Blue	80	66	29.5	1.30	1.51
	90	67	31.5	1.35	1.56
	100	68	33.2	1.38	1.60
	110	69	35.6	1.44	1.66
33 * Gray	80	68	36.2	1.51	1.74
	90	69	38.2	1.54	1.78
	100	70	40.4	1.59	1.83
	110	71	42.6	1.63	1.88
38 * Red	80	72	40.6	1.51	1.74
	90	73	43.0	1.55	1.79
	100	75	45.4	1.55	1.79
	110	76	47.6	1.59	1.83
43 * Dk. Brown	80	74	46.1	1.62	1.87
	90	74	48.5	1.70	1.97
	100	75	50.7	1.74	2.00
	110	77	53.4	1.73	2.00
48 * Dk. Green	80	77	50.2	1.63	1.88
	90	79	52.6	1.62	1.87
	100	81	55.1	1.62	1.87
	110	82	57.5	1.65	1.90
53 * Dk. Blue*	80	81	54.9	1.61	1.86
	90	84	57.2	1.56	1.80
	100	86	59.5	1.55	1.79
	110	87	62.1	1.58	1.82
	120	88	64.4	1.60	1.85
63 * Black	80	86	62.3	1.62	1.87
	90	88	65.5	1.63	1.88
	100	90	69.0	1.64	1.89
	110	91	71.9	1.67	1.93
	120	92	74.7	1.70	1.96
73 * Orange	80	89	72.7	1.77	2.04
	90	91	75.4	1.75	2.02
	100	93	78.1	1.74	2.01
	110	95	80.9	1.73	1.99
	120	97	83.8	1.71	1.98

* Factory installed nozzle

Notes:

All precipitation rates calculated for 180 degree operation. For the precipitation rate for a 360 degree sprinkler, divide by 2.

I-90-36V NOZZLE PERFORMANCE DATA

Nozzle	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM	■	▲
25 • Lt. Blue	80	73	30.5	0.55	0.64
	90	75	32.4	0.55	0.64
	100	76	34.3	0.57	0.66
	110	78	36.5	0.58	0.67
33 • Grey	80	77	36.3	0.59	0.68
	90	78	38.4	0.61	0.7
	100	80	40.6	0.61	0.71
	110	81	42.7	0.63	0.72
38 • Red	80	80	40.6	0.61	0.71
	90	82	42.9	0.61	0.71
	100	83	45.3	0.63	0.73
	110	85	47.7	0.64	0.73
43 • Dk. Brown	80	83	46.2	0.65	0.75
	90	84	48.6	0.66	0.77
	100	85	50.9	0.68	0.78
	110	86	53.4	0.69	0.8
48 • Dk. Green	80	86	49.6	0.65	0.75
	90	89	52.5	0.64	0.74
	100	90	54.8	0.65	0.75
	110	91	57.3	0.67	0.77
53 • Dk. Blue*	80	89	54.2	0.66	0.76
	90	90	56.7	0.67	0.78
	100	92	59.2	0.67	0.78
	110	93	61.7	0.69	0.79
	120	94	64.2	0.7	0.81
63 • Black	80	92	63.2	0.72	0.83
	90	94	65.9	0.72	0.83
	100	96	69.4	0.72	0.84
	110	97	72	0.74	0.85
	120	98	74.9	0.75	0.87
73 • Orange	80	96	72.1	0.75	0.87
	90	98	75	0.75	0.87
	100	99	77.8	0.76	0.88
	110	102	80.5	0.74	0.86
	120	103	83.3	0.76	0.87

* Factory installed nozzle.

Notes:

Precipitation rates for 36V models are calculated for 360-degree operation. All triangular rates are equilateral. For low angle nozzle performance, reduce radius by 15%. Complies to ASAE standard.

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/irrigation-product/rotors/i-90>
071724