

# HC Flow Meter

Detect, monitor, and report critical flow zone data and total system flows with this robust and simple-to-install flow sensor. Add wireless flow-monitoring capabilities to Hydrowise systems with a simple and affordable communication kit.

## КЛЮЧЕВЫЕ ПРЕИМУЩЕСТВА

- Compatible with HC, HPC, Pro-HC, and HCC Controllers
- Compatible with ICC2 Controller via Centralus™ communication modules
- Flow Rate: 0.83 to 500 l/min (depending on size)
- Provides station-level flow rates and totals in Hydrowise Software
- Sends automatic alerts in the event of high-flow, low-flow, or unscheduled flow conditions
- Flow reports within Hydrowise Software can display total system water use and individual station water use for accurate water budgeting and tracking
- Robust brass construction with union fittings for easy installation and removal for winterisation
- Analogue dial on the face of the metre displays daily flow totals and a leak detector
- Optional wireless communication kit available for use with any HC Flow Meter and Hydrowise-enabled HC, HPC, Pro-HC, or HCC Controllers



## HC FLOW METER SPECIFICATIONS

	<b>HC-075-FLOW-B (20 mm)</b>	<b>HC-100-FLOW-B (25 mm)</b>	<b>HC-150-FLOW-B (40 mm)</b>	<b>HC-200-FLOW-B (50 mm)</b>
Minimum flow (l/min)	0.83	1.16	3.33	7.5
Maximum recommended flow (l/min)	60	110	250	400
Maximum flow rate (l/min)	80	130	330	500
Dial reading (m <sup>3</sup> )	1 pulse per 1 l	1 pulse per 10 l	1 pulse per 10 l	1 pulse per 10 l

## Operating Specifications

- Scaled pulse output is precalibrated from the factory based on the size of the meter
- Meter must be hardwired to the controller via shielded, minimum 0.75 mm<sup>2</sup> wire, up to 300 m from the controller
- Accuracy: ± 2% of reading at recommended flow
- Warranty period: 2 years

## Wireless Operating Specifications

- 152 m range (line of sight) from transmitter to receiver
- Communication frequency: 868 MHz for international models
- Communication frequency: 915 MHz for AU/NZ models
- Transmitter power supply: 3 AA batteries
- Receiver power supply: 24 VAC from host controller

## Approvals

- FCC, CE, and RCM approved
- Transmitter is IP68 rated
- Receiver is IP44 rated

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/ru/irrigation-product/datchiki-pogody/hc-flow-meter>  
071724